



Technical data sheet

Single Coat 5000

Product description

An natural oil based finish with an addition of natural waxes. Has a transparent or colored appearance.

Technical data

Color	Transparent or colored
Glos	Semi glos
Density	± 0,940 g/ml
Viscosity	± 100 mPas

Application

For treatment of wooden surfaces like floorings.

Pre treatment

Wooden surfaces must be sanded or planed in advance. Use maximal sanding grid of #120. If you use a trio sanding machine use sanding grid #100 maximum.

Application of use

The finishing always consist of one layer, colored or natural.

Brush or Roller

Approximately 40 – 50 m² / liter

Drying times

After is 24 – 36 hours at temperature of 15 – 25 °C the floor is dust and walk proof.

But complete hardening takes at least three weeks. In this period, the floor is still vulnerable to moisture and corrosive agents. Only clean the floor in the first three weeks using a vacuum cleaner or duster.

For optimal drying time the product must dry in a well ventilated area with a constant temperature of 20 °C. Drying times will take longer when there is a constant humidity of 95 – 99 %

Maintenance

Use Vesting maintenance oil, Vesting Wax & Clean and Vesting Intensive cleaner, read the instructions carefully.

Product information

Shelflife: 1 year in closed packaging. When opened Shelf life is one month.

Dilution: not needed, the product is ready for use.

Special information

Clean machines with acetone, white spirit, turpentine.

WARNING! SELF-IGNITION Lumps, brushes, disks etc. with oil, must be immersed in water and dried in open air!
Otherwise there is a risk of fire!

Wasziederij "De Vesting"
Trasweg 12
NL-5712 BB Someren-Eind
Nederland
Tel: +31 493 496760
Fax: +31 493 493670

www.vesting.nl

01-03-2018-GB