according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article No.: 230-006931 VINTAGE DRIFT

 Print date:
 12.03.2014
 Revision date: 11.03.2014
 EN

 Version:
 6.0
 Issue date: 11.03.2014
 Page 1 / 7



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier) 230-006931
Identification of the substance or mixture VINTAGE DRIFT

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Debal Coatings NV

Industrieweg 29 Telephone: +32 51 30 11 40 B-8800Beveren-Roeselare Telefax: +32 51 26 48

Dept. responsible for information:

Labo:

E-mail (competent person) info@debalcoatings.be

1.4. Emergency telephone number

Emergency telephone number +32 51 30 11 40

(opening hours Monday to Friday from 8:00 am to 4:30 pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

This mixture is classified as hazardous according to 1999/45/EC.

C; R34 Corrosive Causes burns.

2.2. Label elements

Labelling (67/548/EEC or 1999/45/EC)

1 1

C Corrosive

Hazard statements

34 Causes burns.

Precautionary statements

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
38 In case of insufficient ventilation, wear suitable respiratory equipment.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where

possible).

23 Do not breathe vapour.

contains:

sodium hydroxide

Special provisions concerning the labelling of certain mixtures

n.a.

2.3. Other hazards

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Product description / chemical characterization

Description

Hazardous ingredients

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification	Wt % Remark
215-185-5	01-2119457892-27	
1310-73-2	sodium hydroxide	1 - 2,5
011-002-00-6	Met. Corr. 1 H290 / Skin Corr. 1A H314	

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

5 5 ()

Article No.: 230-006931 VINTAGE DRIFT

Print date: 12.03.2014 Revision date: 11.03.2014 Version: 6.0 Revision date: 11.03.2014



EN Page 2 / 7

EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification	Remark
215-185-5	01-2119457892-27	
1310-73-2	sodium hydroxide	1 - 2,5
011-002-00-6	C; R35	

Additional information

Full text of R-phrases: see section 16. Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

230-006931 Article No.: VINTAGE DRIFT

Revision date: 11.03.2014 Print date: 12.03.2014 Version: Issue date: 11.03.2014

ΕN Page 3 / 7



agents. Do not use solvents.

Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eves and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke, Personal protection equipment; refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO), Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limit values:

sodium hydroxide

INDEX No. 011-002-00-6 / EC No. 215-185-5 / CAS No. 1310-73-2

WEL, STEL: 2 mg/m3 Additional information

TWA: long-term occupational exposure limit value STEL: short-term occupational exposure limit value

Ceiling: peak limitation

Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber Thickness of the glove material > 0,4 mm; Breakthrough time (maximum wearing time) > 480 min.

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article No.: 230-006931 VINTAGE DRIFT

Print date: 12.03.2014 Revision date: 11.03.2014 Version: 6.0 Revision date: 11.03.2014

EN Page 4 / 7



Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state liquid
Colour as labeled
Odour characteristic

Safety relevant basis data		Unit	Method	Remark
Flash point (°C):	n.a.			
Ignition temperature in °C:	n.a.			
lower explosion limit:	n.b.			
Upper explosion limit:	n.b.			
Vapour pressure at 20 °C:	n.b.			
Density at 20 °C:	1,10	g/cm³		
Water solubility (g/L):	water-misible			
pH value at 20 °C:	-			
Viscosity at 20 °C:	14 s 4 mm		DIN 53211	
Solvent separation test (%):	< 3	%	ADR/RID	
Solid content (%):	13,19	Wt %		
solvent content:				
Organic solvents:	0,0	Wt %		
Water:	86,8	Wt %		

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Toxicological data are not available.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

230-006931 Article No.: VINTAGE DRIFT

Revision date: 11.03.2014 Print date: 12.03.2014 Version: Issue date: 11.03.2014



ΕN Page 5 / 7

Irritant and corrosive effects

Toxicological data are not available.

Sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this preparation do not meet the criteria for classification as CMR category 1 or 2 according to 67/548/EEC.

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

SECTION 12: Ecological information

overall evaluation

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

12.1. Toxicity

No information available.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111

waste paint and varnish containing organic solvents or

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article No.: 230-006931 VINTAGE DRIFT

Print date: 12.03.2014 Revision date: 11.03.2014
Version: 6.0 Issue date: 11.03.2014



EN Page 6 / 7

other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

1760

14.2. UN proper shipping name

Land transport (ADR/RID): BIJTENDE VLOEISTOF, N.E.G. (NATRIUMHYDROXIDE OPLOSSING)

Sea transport (IMDG): CORROSIVE LIQUID, N.O.S.

(SODIUM HYDROXIDE SOLUTION)

Air transport (ICAO-TI / IATA-DGR): Corrosive liquid, n.o.s.

(SODIUM HYDROXIDE SOLUTION)

14.3. Transport hazard class(es)

8

14.4. Packing group

Ш

14.5. Environmental hazards

Land transport (ADR/RID) n.a.

Marine pollutant n.a.

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Additional information

Land transport (ADR/RID)

tunnel restriction code E

Sea transport (IMDG)

EmS-No. F-A, S-B

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

 VOC-value (in g/L) ISO 11890-2:
 0,042

 VOC-value (in g/L) ASTM D 2369:
 1,258

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No.	Chemical name	REACH No.		
CAS No.				
215-185-5	sodium hydroxide	01-2119457892-27		
1310-73-2	•			

SECTION 16: Other information

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article No.: 230-006931 VINTAGE DRIFT

 Print date:
 12.03.2014
 Revision date: 11.03.2014

 Version:
 6.0
 Issue date: 11.03.2014



EN Page 7 / 7

Relevant R-and H-phrases (Number and full text):

Met. Corr. 1 / H290 Corrosive to metals May be corrosive to metals.

Skin Corr. 1A / H314 skin corrosion/irritation Causes severe skin burns and eye damage.

C; R35 Corrosive Causes severe burns.

Additional information

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.